

CALIBER: 350 Legend - Standard OAL
 MUZZLE VELOCITY: 2600 fps
 BULLET WEIGHT: 140 gr.
 BALLISTIC COEFFICIENT: 0.150
 SIGHT HT.: 1.6 in.
 ZEROED AT: 167.1 Yds.
 INCLINE ANGLE: 0 deg.
 WIND: from 9 O'clock at 4 mph
 ATMOSPHERE: Std. 1000 Ft.
 55.4° F./1000 ft./28.45 in. HG/78% R.H.
 'G1' STANDARD FLAT BASE

Range Yards	Vel. fps	Energy Ft.Lbs.	Drop Inches	Path Inches	Defl. Inches	Time Sec.
0	2,600	2,101	0.0	-1.6	0.0	0.00
25	2,459	1,879	0.2	-0.1	0.1	0.03
50	2,322	1,676	0.7	1.0	0.2	0.06
75	2,190	1,491	1.6	1.7	0.6	0.09
100	2,062	1,321	3.0	2.0	1.0	0.13
125	1,938	1,168	4.9	1.8	1.6	0.17
150	1,819	1,029	7.4	0.9	2.4	0.21
175	1,705	904	10.5	-0.6	3.4	0.25
200	1,597	793	14.4	-2.8	4.5	0.30
225	1,496	695	19.1	-5.9	5.9	0.34
250	1,401	610	24.8	-9.9	7.5	0.40
275	1,314	537	31.6	-15.1	9.4	0.45
300	1,237	475	39.7	-21.5	11.5	0.51
325	1,169	425	49.2	-29.3	13.9	0.57
350	1,111	384	60.3	-38.8	16.5	0.64

FOR A VITAL ZONE OF 4 IN., SET ZERO RANGE TO 167.1 yds.
 MAXIMUM POINT-BLANK RANGE WILL THEN BE 192.4 yds.
 TRAJECTORY CROSSES LINE OF SIGHT AT 27.2 & 167.1 yds.
 PATH IS 2 IN. OVER LINE OF SIGHT AT 102.1 yds.

