

CALIBER: 350 Legend HV - Pointed Ballistic Tip - Extended Range

MUZZLE VELOCITY: 2600 fps

BULLET WEIGHT: 140 gr.

BALLISTIC COEFFICIENT: 0.210

SIGHT HT.: 1.6 in.

ZEROED AT: 176.7 Yds.

INCLINE ANGLE: 0 deg.

WIND: from 9 O'clock at 4 mph

ATMOSPHERE: Std. 1000 Ft.

55.4° F./1000 ft./28.45 in. HG/78% R.H.

'G1' STANDARD FLAT BASE

Range Yards	Vel. fps	Energy Ft.Lbs.	Drop Inches	Path Inches	Defl. Inches	Time Sec.
0	2600	2101	0.0	-1.6	0.0	0.00
25	2499	1941	0.2	-0.2	0.0	0.03
50	2400	1790	0.7	1.0	0.2	0.06
75	2303	1649	1.6	1.7	0.4	0.09
100	2208	1516	2.9	2.0	0.7	0.13
125	2116	1392	4.6	1.9	1.1	0.16
150	2026	1276	6.9	1.2	1.6	0.20
175	1938	1167	9.6	0.1	2.3	0.23
200	1852	1067	13.0	-1.6	3.0	0.27
225	1770	973	16.9	-4.0	3.9	0.32
250	1689	887	21.6	-7.0	4.9	0.36
275	1612	808	27.0	-10.9	6.1	0.40
300	1538	736	33.3	-15.5	7.4	0.45
325	1468	670	40.5	-21.1	8.9	0.50
350	1401	610	48.7	-27.7	10.6	0.55
375	1338	557	58.0	-35.3	12.4	0.61
400	1280	509	68.5	-44.2	14.4	0.67

FOR A VITAL ZONE OF 4 IN., SET ZERO RANGE TO 176.7 yds.

MAXIMUM POINT-BLANK RANGE WILL THEN BE 204.5 yds.

TRAJECTORY CROSSES LINE OF SIGHT AT 28 & 176.7 yds.

PATH IS 2 IN. OVER LINE OF SIGHT AT 106.9 yds.



Bear Creek BALLISTICS
Precision Firearms & Ammunition